

MILLBOARD, INC. FIRE TEST REPORT

SCOPE OF WORK

NFPA 268 TESTING ON EXTERIOR WALL ASSEMBLY CONTAINING MILLBOARD, INC. SHADOW LINE+ EXTERIOR CLADDING.

REPORT NUMBER

R6916.02-121-24 R0

TEST DATE(S)

10/29/24

ISSUE DATE

10/31/24


PAGES

15

DOCUMENT CONTROL NUMBER

RT-R-AMER-Test-3566 (01/29/24)

© 2017 INTERTEK



TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

REPORT ISSUED TO

Millboard, Inc.

1330 Lagoon Ave #400
Minneapolis, MN 55408

SECTION 1

SCOPE

Architectural Testing, Inc. (an Intertek company), dba Intertek Building & Construction (B&C) was contracted by Millboard, Inc., Minneapolis, Minnesota to evaluate the performance of exterior walls containing Shadow Line+ when exposed to a radiant heat source. Testing was conducted at the Intertek B&C test facility in York, Pennsylvania. Results obtained are tested values and were secured by using the designated test method(s). A summary of test results and the complete graphical test data is reported herein.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. Intertek will service this report for the entire test record retention period. The test record retention period ends four years after the test date. Test records, such as detailed drawings, datasheets, representative samples of test specimens, or other pertinent project documentation, will be retained for the entire test record retention period.

Unless differently required, Intertek reports apply the "Simple Acceptance" rule, also called "Shared Risk approach," of ILAC-G8:09/2019, Guidelines on Decision Rules and Statements of Conformity.

For INTERTEK B&C:

COMPLETED BY:	Timothy Feltman	REVIEWED BY:	Ethan Grove
TITLE:	Technician – Fire Testing	TITLE:	Sr. Regional Manager
SIGNATURE:		SIGNATURE:	
DATE:	10/31/24	DATE:	10/31/24

TRF:ddr

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 2

SUMMARY OF TEST RESULTS

Wall System: Exterior Wall Assembly

Combustible Components: SPF 2" x 4" wood framing, 7/16" Orientated Strand Board (OSB), Benjamin Obdyke HydroGap® drainable housewrap, Millboard Inc. Shadow Line+ exterior cladding.

NFPA 268 Test Results

The assembly described and tested in this report **did** meet the full, 20-minute exposure duration as required by the NFPA 268 test method. Construction of the full assembly is summarized in Section 7 of this test report.

SECTION 3

TEST METHOD

The assembly was evaluated in accordance with the following:

NFPA 268-2022, Standard Test Method for Determining Ignitability of Exterior Wall Assemblies Using a Radiant Heat Energy Source

SECTION 4

MATERIAL SOURCE/INSTALLATION

The sampled product was selected by Intertek B&C personnel. The specimen was witnessed during production and tagged prior to shipment on 08/15/24, (Reference Intertek B&C Job No. R6916.01-121-38, dated 08/15/24). The remaining components of the test assembly, the wall framing and sheathing was acquired and assembled by Intertek B&C personnel.

SECTION 5

LIST OF OFFICIAL OBSERVERS

NAME	COMPANY
Timothy Feltman	Intertek B&C
Keith Leonhard	Intertek B&C

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 6

TEST PROCEDURE

The test specimen is installed into the test apparatus and centered both vertically and horizontally with respect to the center of the radiant exposure panel. Prior to the initiation of the test, a water-cooled radiation barrier is placed between the radiant panel and test specimen to absorb the energy from the radiant burner once the calibrated exposure is achieved. Thirty seconds after the spark igniter, located 5/8 inch away from the exposed face of the specimen, is energized, the radiation shield is removed, and the test begins with the sample being subjected to the calibrated exposure. The igniter is cycled on for greater than 5 seconds and off for less than 2 seconds to create a piloted ignition source. The test is continued for 20 minutes, or until sustained flaming for a period of 5 seconds or more occurs within the 20-minute test duration.

SECTION 7

TEST ASSEMBLY DESCRIPTION

The overall dimensions of the test assembly are 4 feet wide by 8 feet high. Below is a detailed description of the components in the assembly:

Framing

SPF 2" x 4" wood studs' space 16" on center were fastened with 3 1/4" long framing nails.

Exterior Sheathing

7/16" thick OSB was fastened to the wood framing using 2 3/8" nails every 8" around the perimeter and every 12" in the field.

Water-resistive Barrier

Benjamin Obdyke HydroGap® drainable house wrap was stapled to the exterior sheathing using T50 3/8" staples. A 4 1/2" overlap was utilized.

Exterior Cladding

Millboard Inc. Shadow Line+ was horizontally installed and fastened every 24" on the tongue using 6d siding nails.

Note: The test specimen was conditioned to a constant weight at 21.1°C ± 5.6°C (70°F ± 10°F) and a relative humidity of 50 percent ± 10 percent.

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 8

TEST OBSERVATIONS

Calibration Information:

Calibration Date: 10/09/2024

Average Heat Flux of Four Quadrant Heat Flux Transducers: 12.4 kW/m²

The heat flux at the center of the calibration panel shall not exceed 15kW/m² nor be less than 12.5kW/m²; True; Low: 13.8kW/m², High: 14.8 kW/m²

Average Surface Temperature of Radiant Panel: 1571 °F

Test Date: 10/29/2024

Lab Temperature: 61 °F

Lab Relative Humidity: 44%

TIME (Min:Sec)	OBSERVATIONS
Pre-test (-10:00)	Ignition of radiant panel burner.
Pre-test (-01:00)	Data acquisition begins.
Pre-test (-00:30)	Spark igniter initiated
00:00	Radiation shield removed. Test begins.
00:45	Smoke emitting from test assembly
02:51	Bubbling of exposed surface
09:11	Charring of exposed surface
10:03	Transient flaming at the spark ignitor; not sustained
20:00	End of Test

SECTION 9

TEST RESULTS

TEST REQUIREMENTS	TEST RESULTS	PASS/FAIL
Sustained flaming (ignition) for a period of 5 seconds or more shall not occur within the 20-minute test period.	Sustained flaming did not occur during the 20-minute test period.	PASS

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 10(Continued)

PHOTOGRAPHS




Photo No. 1
Stamped Product Information




Photo No. 2
Product Sampling Marks

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 10 PHOTOGRAPHS



Photo No. 3
Wall Framing Spaced 16" on Center



Photo No. 4
7/16" OSB

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 10 (Continued)

PHOTOGRAPHS



Photo No. 5
Addition of HydroGap®



Photo No. 6
4 1/2" Overlap

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 10 (Continued)

PHOTOGRAPHS



Photo No. 5
Complete Assembly



Photo No. 6
Complete Assembly Pre-test

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 10(Continued)

PHOTOGRAPHS



Photo No. 7
Initiation of Test



Photo No. 8
Smoke Emitting from Test Assembly

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 10(Continued)

PHOTOGRAPHS



Photo No. 9
Bubbling of Exposed Surface



Photo No. 10
Charring of Exposed Surface

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 10(Continued) PHOTOGRAPHS



Photo No. 11
Post Test


TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 11

GRAPHS



Graph No. 1
Burner Output Verification Data


TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 11 (CONTINUED)

GRAPHS



Graph No. 2
Reference Heat Flux



Total Quality. Assured.

130 Derry Court
York, Pennsylvania 17406

Telephone: 717-764-7700
Facsimile: 717-764-4129
www.intertek.com/building

TEST REPORT FOR MILLBOARD, INC.

Report No.: R6916.02-121-24 R0

Date: 10/31/24

SECTION 12

REVISION LOG

REVISION #	DATE	PAGES	REVISION
0	10/31/24	N/A	Original Report Issue